DERBIPAIN1

Matt acrylic paint for finishing bituminous membranes

Description

DERBIPAINT E is a water based acrylic paint mainly applied for aesthetic reasons on smooth waterproofing membranes.

Advantages

- Available in different colors
- Improves aesthetics of waterproofing membranes
- Offers extra UV protection
- White and light grey form a heat shield, reducing surface temperature considerably
- Safe to use and environmentally friendly in all circumstances
- Water based emulsion, thus contains no solvent (not flammable)
- Provides effective protection against moss development
- Improves the quality of recycled rainwater
- Dries quickly
- Application suitable on all types of weathered bituminous membranes
- Combines additional protection and aesthetics

Colours

White, light grey, black, terracotta

Usage

Consumption: - On new, smooth roofing membrane:

 $5~\text{m}^2/\text{I/coat}$ (degrease first with cleanig product and water), apply 2 coats

- On older roofing membrane : Plain: 5 m²/l/coat, apply 2 coats

With sand or granules: first layer 20% thinned with water: 2.5 - 3.5 m²/l

second layer, not thinned: 3.5 m²/l

Equipment: - roller or brush

- airless spraygun with a 36/50 or 31/40 Spray tip for large surfaces and 27/40

for small surfaces

Cleaning material: immediately after use with water Processing conditions: Drying time: dustfree: 1 hour

rain free: 6 hours repaint: 6 hours hardening: 24 hours

Frostfree: 24 hours after application

Substrate Temp.: min. 5 °C min. 5 °C Ambiant Temp. :

Packaging

Can of: 10 I 20 I

Technical data

Density: 1,3 - 1,4 kg/lNon volatiles : 65 % Flashpoint Pensky Martens cc: not applicable

Storage

Shelf-life (in unopened airtight cans): 12 months. Protected from frost, with temperature from 5 to 35 °C.



RAI 7035



WWW.DERBIGUM.COM



IMPERBEL SA/NV

Bergensesteenweg 32 – 1651 Lot – Belgium Tel.: +32 2 334 87 19 Fax: +32 2 378 40 42

E-mail: info@imperbel.be